



## Multi/Clamp

### → Your benefits

- Quick and easy installation
- Suitable for under pressure repair
- Wide variety of stainless steel repair clamps and tapping tees
- Durable and free from corrosion thanks to stainless steel body
- Reusable
- Applicable for under- and above-ground use



## Contents Multi/Clamp

	pagina
Multi/Clamp Snap	92
Multi/Clamp Midi	95
Multi/Clamp Single	97
Multi/Clamp Double	103
Multi/Clamp Triple	109
Multi/Clamp Thread	112
Multi/Clamp Saddle Studs	112
Multi/Clamp Flange	115
Multi/Clamp Combi Box	119

# Multi/Clamp

## Multi/Clamp Snap length 75 mm



### Model:

- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- Lugs are made of ductile cast iron
- The rubber gasket is available in NBR (EPDM on request)
- The rubber gasket is clamped and partially covers the inside of the band

Range [mm]	PN Water [bar]	NBR Code	kg
15 - 22	16.0	<b>724 208 010</b>	0.300
21 - 25	16.0	<b>724 208 019</b>	0.300
26 - 30	16.0	<b>724 208 028</b>	0.300
33 - 37	16.0	<b>724 208 037</b>	0.300
37 - 41	16.0	<b>724 208 046</b>	0.300
42 - 45	16.0	<b>724 208 055</b>	0.400
48 - 51	16.0	<b>724 208 064</b>	0.400
50 - 54	16.0	<b>724 208 073</b>	0.400
55 - 58	16.0	<b>724 208 082</b>	0.400
60 - 64	16.0	<b>724 208 091</b>	0.400
62 - 66	16.0	<b>724 208 100</b>	0.400
65 - 69	16.0	<b>724 208 109</b>	0.400
69 - 73	16.0	<b>724 208 118</b>	0.400
71 - 76	16.0	<b>724 208 127</b>	0.400
74 - 80	16.0	<b>724 208 136</b>	0.500
87 - 93	16.0	<b>724 208 145</b>	0.500
94 - 100	16.0	<b>724 208 154</b>	0.500
99 - 104	16.0	<b>724 208 163</b>	0.500
105 - 111	16.0	<b>724 208 172</b>	0.600
112 - 117	10.0	<b>724 208 181</b>	0.600
115 - 121	10.0	<b>724 208 190</b>	0.600
120 - 126	10.0	<b>724 208 199</b>	0.600
126 - 131	10.0	<b>724 208 208</b>	0.700
131 - 136	10.0	<b>724 208 217</b>	0.700
139 - 145	10.0	<b>724 208 226</b>	0.700
149 - 155	10.0	<b>724 208 235</b>	0.800
156 - 162	10.0	<b>724 208 244</b>	0.800
167 - 173	10.0	<b>724 208 253</b>	0.800
173 - 179	10.0	<b>724 208 262</b>	0.800
200 - 206	10.0	<b>724 208 271</b>	0.900
217 - 223	10.0	<b>724 208 280</b>	0.900
223 - 229	10.0	<b>724 208 289</b>	1.001
272 - 278	6.0	<b>724 208 298</b>	1.001
323 - 329	6.0	<b>724 208 307</b>	1.200

PF 1 54 325 010



## Multi/Clamp Snap length 150 mm

### Model:

- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- Lugs are made of ductile cast iron
- The rubber gasket is available in NBR (EPDM on request)
- The rubber gasket is clamped and partially covers the inside of the band

Range [mm]	PN Water [bar]	NBR Code	kg	
15 - 22	16.0	<b>724 208 011</b>	0.500	
21 - 25	16.0	<b>724 208 020</b>	0.600	
26 - 30	16.0	<b>724 208 029</b>	0.600	
33 - 37	16.0	<b>724 208 038</b>	0.600	
37 - 41	16.0	<b>724 208 047</b>	0.600	
42 - 45	16.0	<b>724 208 056</b>	0.700	
48 - 51	16.0	<b>724 208 065</b>	0.700	
50 - 54	16.0	<b>724 208 074</b>	0.700	
55 - 58	16.0	<b>724 208 083</b>	0.700	
60 - 64	16.0	<b>724 208 092</b>	0.800	
62 - 66	16.0	<b>724 208 101</b>	0.800	
65 - 69	16.0	<b>724 208 110</b>	0.800	
69 - 73	16.0	<b>724 208 119</b>	0.800	
71 - 76	16.0	<b>724 208 128</b>	0.800	
74 - 80	16.0	<b>724 208 137</b>	0.900	
87 - 93	16.0	<b>724 208 146</b>	1.001	
94 - 100	16.0	<b>724 208 155</b>	1.001	
99 - 104	16.0	<b>724 208 164</b>	1.001	
105 - 111	16.0	<b>724 208 173</b>	1.100	
112 - 117	10.0	<b>724 208 182</b>	1.100	
115 - 121	10.0	<b>724 208 191</b>	1.100	
120 - 126	10.0	<b>724 208 200</b>	1.100	
126 - 131	10.0	<b>724 208 209</b>	1.200	
131 - 136	10.0	<b>724 208 218</b>	1.200	
139 - 145	10.0	<b>724 208 227</b>	1.200	
149 - 155	10.0	<b>724 208 236</b>	1.300	
156 - 162	10.0	<b>724 208 245</b>	1.300	
167 - 173	10.0	<b>724 208 254</b>	1.300	
173 - 179	10.0	<b>724 208 263</b>	1.300	
200 - 206	10.0	<b>724 208 272</b>	1.400	
217 - 223	10.0	<b>724 208 281</b>	1.400	
223 - 229	10.0	<b>724 208 290</b>	1.500	
272 - 278	6.0	<b>724 208 299</b>	1.500	
323 - 329	6.0	<b>724 208 308</b>	1.700	

PF 1 54 325 010



## Multi/Clamp Snap length 225 mm

### Model:

- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- Lugs are made of ductile cast iron
- The rubber gasket is available in NBR (EPDM on request)
- The rubber gasket is clamped and partially covers the inside of the band

Range [mm]	PN Water [bar]	NBR Code	kg
15 - 22	16.0	<b>724 208 012</b>	0.800
21 - 25	16.0	<b>724 208 021</b>	0.800
26 - 30	16.0	<b>724 208 030</b>	0.900
33 - 37	16.0	<b>724 208 039</b>	0.900
37 - 41	16.0	<b>724 208 048</b>	0.900
42 - 45	16.0	<b>724 208 057</b>	1.001
48 - 51	16.0	<b>724 208 066</b>	1.001
50 - 54	16.0	<b>724 208 075</b>	1.001
55 - 58	16.0	<b>724 208 084</b>	1.100
60 - 64	16.0	<b>724 208 093</b>	1.100
62 - 66	16.0	<b>724 208 102</b>	1.100
65 - 69	16.0	<b>724 208 111</b>	1.200
69 - 73	16.0	<b>724 208 120</b>	1.200
71 - 76	16.0	<b>724 208 129</b>	1.200
74 - 80	16.0	<b>724 208 138</b>	1.300
87 - 93	16.0	<b>724 208 147</b>	1.400
94 - 100	16.0	<b>724 208 156</b>	1.500
99 - 104	16.0	<b>724 208 165</b>	1.500
105 - 111	16.0	<b>724 208 174</b>	1.600
112 - 117	10.0	<b>724 208 183</b>	1.600
115 - 121	10.0	<b>724 208 192</b>	1.600
120 - 126	10.0	<b>724 208 201</b>	1.600
126 - 131	10.0	<b>724 208 210</b>	1.700
131 - 136	10.0	<b>724 208 219</b>	1.700
139 - 145	10.0	<b>724 208 228</b>	1.700
149 - 155	10.0	<b>724 208 237</b>	1.800
156 - 162	10.0	<b>724 208 246</b>	1.800
167 - 173	10.0	<b>724 208 255</b>	1.800
173 - 179	10.0	<b>724 208 264</b>	1.800
200 - 206	10.0	<b>724 208 273</b>	1.900
217 - 223	10.0	<b>724 208 282</b>	1.900
223 - 229	10.0	<b>724 208 291</b>	2.000
272 - 278	6.0	<b>724 208 300</b>	2.000
323 - 329	6.0	<b>724 208 309</b>	2.200

PF 1 54 325 010



## Multi/Clamp Midi length 100 mm

### Model:

- Single band clamp with partial gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg	
19 - 23	16.0	<b>724 209 010</b>	0.600	
25 - 29	16.0	<b>724 209 019</b>	0.600	
32 - 36	16.0	<b>724 209 028</b>	0.600	
38 - 42	16.0	<b>724 209 037</b>	0.600	
44 - 51	16.0	<b>724 209 046</b>	0.800	
48 - 55	16.0	<b>724 209 055</b>	1.050	
54 - 58	16.0	<b>724 209 064</b>	0.900	
60 - 64	16.0	<b>724 209 073</b>	1.050	
63 - 70	16.0	<b>724 209 082</b>	1.120	
67 - 74	16.0	<b>724 209 091</b>	1.120	
70 - 77	16.0	<b>724 209 100</b>	1.120	
73 - 80	16.0	<b>724 209 109</b>	1.120	
75 - 83	16.0	<b>724 209 118</b>	1.120	
82 - 90	16.0	<b>724 209 127</b>	1.200	
87 - 97	16.0	<b>724 209 136</b>	1.200	
95 - 104	16.0	<b>724 209 145</b>	1.200	
98 - 108	16.0	<b>724 209 154</b>	1.200	
102 - 112	16.0	<b>724 209 163</b>	1.350	
108 - 118	16.0	<b>724 209 172</b>	1.350	
113 - 123	16.0	<b>724 209 181</b>	1.350	
118 - 128	16.0	<b>724 209 190</b>	1.350	
120 - 131	16.0	<b>724 209 199</b>	1.350	

PF 1 54 325 009



## Multi/Clamp Midi length 150 mm

### Model:

- Single band clamp with partial gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg	
54 - 58	16.0	<b>724 209 065</b>	1.400	
60 - 64	16.0	<b>724 209 074</b>	1.400	
63 - 70	16.0	<b>724 209 083</b>	1.500	
67 - 74	16.0	<b>724 209 092</b>	1.500	
70 - 77	16.0	<b>724 209 101</b>	1.500	
73 - 80	16.0	<b>724 209 110</b>	1.500	
75 - 83	16.0	<b>724 209 119</b>	1.500	
82 - 90	16.0	<b>724 209 128</b>	1.600	
87 - 97	16.0	<b>724 209 137</b>	1.600	
95 - 104	16.0	<b>724 209 146</b>	1.600	
98 - 108	16.0	<b>724 209 155</b>	1.600	
102 - 112	16.0	<b>724 209 164</b>	1.800	
108 - 118	16.0	<b>724 209 173</b>	1.800	
113 - 123	16.0	<b>724 209 182</b>	1.800	
118 - 128	16.0	<b>724 209 191</b>	1.800	
120 - 131	16.0	<b>724 209 200</b>	1.800	
125 - 135	16.0	<b>724 209 209</b>	2.100	
133 - 144	16.0	<b>724 209 218</b>	2.100	
139 - 150	16.0	<b>724 209 227</b>	2.100	
145 - 155	16.0	<b>724 209 236</b>	2.100	
151 - 161	16.0	<b>724 209 245</b>	2.200	
159 - 170	16.0	<b>724 209 254</b>	2.200	
165 - 175	16.0	<b>724 209 263</b>	2.200	
168 - 180	16.0	<b>724 209 272</b>	2.200	
176 - 186	10.0	<b>724 209 281</b>	2.600	

PF 1 54 325 009



## Multi/Clamp Midi length 200 mm

### Model:

- Single band clamp with partial gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
95 - 104	16.0	<b>724 209 147</b>	2.000
98 - 108	16.0	<b>724 209 156</b>	2.000
102 - 112	16.0	<b>724 209 165</b>	2.200
108 - 118	16.0	<b>724 209 174</b>	2.200
113 - 123	16.0	<b>724 209 183</b>	2.200
118 - 128	16.0	<b>724 209 192</b>	2.200
120 - 131	16.0	<b>724 209 201</b>	2.200
125 - 135	16.0	<b>724 209 210</b>	2.600
133 - 144	16.0	<b>724 209 219</b>	2.600
139 - 150	16.0	<b>724 209 228</b>	2.600
145 - 155	16.0	<b>724 209 237</b>	2.600
151 - 161	16.0	<b>724 209 246</b>	2.800
159 - 170	16.0	<b>724 209 255</b>	2.800
165 - 175	16.0	<b>724 209 264</b>	2.800
168 - 180	16.0	<b>724 209 273</b>	2.800
176 - 186	10.0	<b>724 209 282</b>	3.200
180 - 191	10.0	<b>724 209 291</b>	3.200
193 - 203	10.0	<b>724 209 300</b>	3.200
200 - 210	10.0	<b>724 209 309</b>	3.500
209 - 220	10.0	<b>724 209 318</b>	3.600

PF 1 54 325 009





## Multi/Clamp Single length 75 mm

### Model:

- Single band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
19 - 23	16.0	<b>724 211 010</b>	0.400
25 - 29	16.0	<b>724 211 026</b>	0.400
32 - 36	16.0	<b>724 211 042</b>	0.400
38 - 42	16.0	<b>724 211 058</b>	0.400

PF 1 54 325 009



## Multi/Clamp Single length 150 mm

### Model:

- Single band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
19 - 23	16.0	<b>724 211 011</b>	0.800
25 - 29	16.0	<b>724 211 027</b>	0.800
32 - 36	16.0	<b>724 211 043</b>	0.800
38 - 42	16.0	<b>724 211 059</b>	0.800
44 - 51	16.0	<b>724 211 075</b>	1.400
48 - 55	16.0	<b>724 211 091</b>	1.400
52 - 59	16.0	<b>724 211 107</b>	1.400
57 - 64	16.0	<b>724 211 123</b>	1.400
60 - 67	16.0	<b>724 211 139</b>	1.400
63 - 70	16.0	<b>724 211 155</b>	1.500
67 - 74	16.0	<b>724 211 171</b>	1.500
70 - 77	16.0	<b>724 211 187</b>	1.500
73 - 80	16.0	<b>724 211 203</b>	1.500
75 - 83	16.0	<b>724 211 219</b>	1.500
82 - 90	16.0	<b>724 211 235</b>	1.600
87 - 97	16.0	<b>724 211 251</b>	1.600
95 - 104	16.0	<b>724 211 267</b>	1.600
98 - 108	16.0	<b>724 211 283</b>	1.600
102 - 112	16.0	<b>724 211 299</b>	1.800
108 - 118	16.0	<b>724 211 315</b>	1.800
113 - 123	16.0	<b>724 211 331</b>	1.800
118 - 128	16.0	<b>724 211 347</b>	1.800
120 - 131	16.0	<b>724 211 363</b>	1.800
125 - 135	16.0	<b>724 211 379</b>	2.100
133 - 144	16.0	<b>724 211 395</b>	2.100
139 - 150	16.0	<b>724 211 411</b>	2.100
145 - 155	16.0	<b>724 211 427</b>	2.100
151 - 161	16.0	<b>724 211 443</b>	2.200
159 - 170	16.0	<b>724 211 459</b>	2.200
165 - 175	16.0	<b>724 211 475</b>	2.200
168 - 180	16.0	<b>724 211 491</b>	2.200

PF 1 54 325 009



## Multi/Clamp Single length 200 mm

### Model:

- Single band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
44 - 51	16.0	<b>724 211 076</b>	1.600
48 - 55	16.0	<b>724 211 092</b>	1.600
52 - 59	16.0	<b>724 211 108</b>	1.700
57 - 64	16.0	<b>724 211 124</b>	1.700
60 - 67	16.0	<b>724 211 140</b>	1.700
63 - 70	16.0	<b>724 211 156</b>	1.800
67 - 74	16.0	<b>724 211 172</b>	1.800
70 - 77	16.0	<b>724 211 188</b>	1.800
73 - 80	16.0	<b>724 211 204</b>	1.800
75 - 83	16.0	<b>724 211 220</b>	1.800
82 - 90	16.0	<b>724 211 236</b>	2.000
87 - 97	16.0	<b>724 211 252</b>	2.000
95 - 104	16.0	<b>724 211 268</b>	2.000
98 - 108	16.0	<b>724 211 284</b>	2.000
102 - 112	16.0	<b>724 211 300</b>	2.200
108 - 118	16.0	<b>724 211 316</b>	2.200
113 - 123	16.0	<b>724 211 332</b>	2.200
118 - 128	16.0	<b>724 211 348</b>	2.200
120 - 131	16.0	<b>724 211 364</b>	2.200
125 - 135	16.0	<b>724 211 380</b>	2.600
133 - 144	16.0	<b>724 211 396</b>	2.600
139 - 150	16.0	<b>724 211 412</b>	2.600
145 - 155	16.0	<b>724 211 428</b>	2.600
151 - 161	16.0	<b>724 211 444</b>	2.800
159 - 170	16.0	<b>724 211 460</b>	2.800
165 - 175	16.0	<b>724 211 476</b>	2.800
168 - 180	16.0	<b>724 211 492</b>	2.800
176 - 186	10.0	<b>724 211 508</b>	3.200
180 - 191	10.0	<b>724 211 524</b>	3.200
193 - 203	10.0	<b>724 211 540</b>	3.200
200 - 210	10.0	<b>724 211 556</b>	3.500
209 - 220	10.0	<b>724 211 572</b>	3.500
215 - 226	10.0	<b>724 211 588</b>	3.500
219 - 230	10.0	<b>724 211 604</b>	3.500
222 - 233	10.0	<b>724 211 620</b>	3.500
228 - 240	10.0	<b>724 211 636</b>	3.800
243 - 253	10.0	<b>724 211 652</b>	3.800
252 - 262	10.0	<b>724 211 668</b>	3.900
261 - 271	10.0	<b>724 211 684</b>	3.900
271 - 281	10.0	<b>724 211 700</b>	3.900
280 - 290	10.0	<b>724 211 716</b>	3.900
294 - 304	10.0	<b>724 211 732</b>	3.900
300 - 310	10.0	<b>724 211 748</b>	4.300
310 - 320	10.0	<b>724 211 764</b>	4.300
315 - 326	10.0	<b>724 211 780</b>	4.300
320 - 330	10.0	<b>724 211 796</b>	4.300
324 - 334	10.0	<b>724 211 812</b>	4.300
335 - 346	10.0	<b>724 211 828</b>	4.300

PF 1 54 325 009



## Multi/Clamp Single length 250 mm

### Model:

- Single band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
60 - 67	16.0	<b>724 211 141</b>	2.300
63 - 70	16.0	<b>724 211 157</b>	2.500
67 - 74	16.0	<b>724 211 173</b>	2.500
70 - 77	16.0	<b>724 211 189</b>	2.500
73 - 80	16.0	<b>724 211 205</b>	2.500
75 - 83	16.0	<b>724 211 221</b>	2.500
82 - 90	16.0	<b>724 211 237</b>	2.700
87 - 97	16.0	<b>724 211 253</b>	2.700
95 - 104	16.0	<b>724 211 269</b>	2.700
98 - 108	16.0	<b>724 211 285</b>	2.700
102 - 112	16.0	<b>724 211 301</b>	3.000
108 - 118	16.0	<b>724 211 317</b>	3.000
113 - 123	16.0	<b>724 211 333</b>	3.000
118 - 128	16.0	<b>724 211 349</b>	3.000
120 - 131	16.0	<b>724 211 365</b>	3.000
125 - 135	16.0	<b>724 211 381</b>	3.400
133 - 144	16.0	<b>724 211 397</b>	3.400
139 - 150	16.0	<b>724 211 413</b>	3.400
145 - 155	16.0	<b>724 211 429</b>	3.400
151 - 161	16.0	<b>724 211 445</b>	3.700
159 - 170	16.0	<b>724 211 461</b>	3.700
165 - 175	16.0	<b>724 211 477</b>	3.700
168 - 180	16.0	<b>724 211 493</b>	3.700
176 - 186	10.0	<b>724 211 509</b>	4.200
180 - 191	10.0	<b>724 211 525</b>	4.200
193 - 203	10.0	<b>724 211 541</b>	4.200
200 - 210	10.0	<b>724 211 557</b>	4.700
209 - 220	10.0	<b>724 211 573</b>	4.700
215 - 226	10.0	<b>724 211 589</b>	4.700
219 - 230	10.0	<b>724 211 605</b>	4.700
222 - 233	10.0	<b>724 211 621</b>	4.700
228 - 240	10.0	<b>724 211 637</b>	4.900
243 - 253	10.0	<b>724 211 653</b>	4.900
252 - 262	10.0	<b>724 211 669</b>	5.200
261 - 271	10.0	<b>724 211 685</b>	5.200
271 - 281	10.0	<b>724 211 701</b>	5.200
280 - 290	10.0	<b>724 211 717</b>	5.200
294 - 304	10.0	<b>724 211 733</b>	5.200
300 - 310	10.0	<b>724 211 749</b>	5.600
310 - 320	10.0	<b>724 211 765</b>	5.600
315 - 326	10.0	<b>724 211 781</b>	5.600
320 - 330	10.0	<b>724 211 797</b>	5.600
324 - 334	10.0	<b>724 211 813</b>	5.600
335 - 346	10.0	<b>724 211 829</b>	5.600

PF 1 54 325 009



## Multi/Clamp Single length 300 mm

### Model:

- Single band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
60 - 67	16.0	<b>724 211 142</b>	2.600
63 - 70	16.0	<b>724 211 158</b>	2.800
67 - 74	16.0	<b>724 211 174</b>	2.800
70 - 77	16.0	<b>724 211 190</b>	2.800
73 - 80	16.0	<b>724 211 206</b>	2.800
75 - 83	16.0	<b>724 211 222</b>	2.800
82 - 90	16.0	<b>724 211 238</b>	3.000
87 - 97	16.0	<b>724 211 254</b>	3.000
95 - 104	16.0	<b>724 211 270</b>	3.000
98 - 108	16.0	<b>724 211 286</b>	3.000
102 - 112	16.0	<b>724 211 302</b>	3.400
108 - 118	16.0	<b>724 211 318</b>	3.400
113 - 123	16.0	<b>724 211 334</b>	3.400
118 - 128	16.0	<b>724 211 350</b>	3.400
120 - 131	16.0	<b>724 211 366</b>	3.400
125 - 135	16.0	<b>724 211 382</b>	4.000
133 - 144	16.0	<b>724 211 398</b>	4.000
139 - 150	16.0	<b>724 211 414</b>	4.000
145 - 155	16.0	<b>724 211 430</b>	4.000
151 - 161	16.0	<b>724 211 446</b>	4.300
159 - 170	16.0	<b>724 211 462</b>	4.300
165 - 175	16.0	<b>724 211 478</b>	4.300
168 - 180	16.0	<b>724 211 494</b>	4.300
176 - 186	10.0	<b>724 211 510</b>	4.900
180 - 191	10.0	<b>724 211 526</b>	4.900
193 - 203	10.0	<b>724 211 542</b>	4.900
200 - 210	10.0	<b>724 211 558</b>	5.400
209 - 220	10.0	<b>724 211 574</b>	5.400
215 - 226	10.0	<b>724 211 590</b>	5.400
219 - 230	10.0	<b>724 211 606</b>	5.400
222 - 233	10.0	<b>724 211 622</b>	5.400
228 - 240	10.0	<b>724 211 638</b>	6.100
243 - 253	10.0	<b>724 211 654</b>	6.100
252 - 262	10.0	<b>724 211 670</b>	6.400
261 - 271	10.0	<b>724 211 686</b>	6.400
271 - 281	10.0	<b>724 211 702</b>	6.400
280 - 290	10.0	<b>724 211 718</b>	6.400
294 - 304	10.0	<b>724 211 734</b>	6.400
300 - 310	10.0	<b>724 211 750</b>	6.900
310 - 320	10.0	<b>724 211 766</b>	6.900
315 - 326	10.0	<b>724 211 782</b>	6.900
320 - 330	10.0	<b>724 211 798</b>	6.900
324 - 334	10.0	<b>724 211 814</b>	6.900
335 - 346	10.0	<b>724 211 830</b>	6.900

PF 1 54 325 009



## Multi/Clamp Single length 400 mm

### Model:

- Single band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
63 - 70	16.0	<b>724 211 159</b>	3.600
67 - 74	16.0	<b>724 211 175</b>	3.600
70 - 77	16.0	<b>724 211 191</b>	3.600
73 - 80	16.0	<b>724 211 207</b>	3.600
75 - 83	16.0	<b>724 211 223</b>	3.600
82 - 90	16.0	<b>724 211 239</b>	3.900
87 - 97	16.0	<b>724 211 255</b>	3.900
95 - 104	16.0	<b>724 211 271</b>	3.900
98 - 108	16.0	<b>724 211 287</b>	3.900
102 - 112	16.0	<b>724 211 303</b>	4.500
108 - 118	16.0	<b>724 211 319</b>	4.500
113 - 123	16.0	<b>724 211 335</b>	4.500
118 - 128	16.0	<b>724 211 351</b>	4.500
120 - 131	16.0	<b>724 211 367</b>	4.500
125 - 135	16.0	<b>724 211 383</b>	5.200
133 - 144	16.0	<b>724 211 399</b>	5.200
139 - 150	16.0	<b>724 211 415</b>	5.200
145 - 155	16.0	<b>724 211 431</b>	5.200
151 - 161	16.0	<b>724 211 447</b>	5.600
159 - 170	16.0	<b>724 211 463</b>	5.600
165 - 175	16.0	<b>724 211 479</b>	5.600
168 - 180	16.0	<b>724 211 495</b>	5.600
176 - 186	10.0	<b>724 211 511</b>	6.400
180 - 191	10.0	<b>724 211 527</b>	6.400
193 - 203	10.0	<b>724 211 543</b>	6.400
200 - 210	10.0	<b>724 211 559</b>	7.100
209 - 220	10.0	<b>724 211 575</b>	7.100
215 - 226	10.0	<b>724 211 591</b>	7.100
219 - 230	10.0	<b>724 211 607</b>	7.100
222 - 233	10.0	<b>724 211 623</b>	7.100
228 - 240	10.0	<b>724 211 639</b>	7.900
243 - 253	10.0	<b>724 211 655</b>	7.900
252 - 262	10.0	<b>724 211 671</b>	8.500
261 - 271	10.0	<b>724 211 687</b>	8.500
271 - 281	10.0	<b>724 211 703</b>	8.500
280 - 290	10.0	<b>724 211 719</b>	8.500
294 - 304	10.0	<b>724 211 735</b>	8.500
300 - 310	10.0	<b>724 211 751</b>	9.000
310 - 320	10.0	<b>724 211 767</b>	9.000
315 - 326	10.0	<b>724 211 783</b>	9.000
320 - 330	10.0	<b>724 211 799</b>	9.000
324 - 334	10.0	<b>724 211 815</b>	9.000
335 - 346	10.0	<b>724 211 831</b>	9.000

PF 1 54 325 009



## Multi/Clamp Single length 500 mm

### Model:

- Single band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
108 - 118	16.0	<b>724 211 320</b>	5.400
113 - 123	16.0	<b>724 211 336</b>	5.400
118 - 128	16.0	<b>724 211 352</b>	5.400
120 - 131	16.0	<b>724 211 368</b>	5.400
125 - 135	16.0	<b>724 211 384</b>	6.700
133 - 144	16.0	<b>724 211 400</b>	6.700
139 - 150	16.0	<b>724 211 416</b>	6.700
145 - 155	16.0	<b>724 211 432</b>	6.700
151 - 161	16.0	<b>724 211 448</b>	7.200
159 - 170	16.0	<b>724 211 464</b>	7.200
165 - 175	16.0	<b>724 211 480</b>	7.200
168 - 180	16.0	<b>724 211 496</b>	7.200
176 - 186	10.0	<b>724 211 512</b>	8.200
180 - 191	10.0	<b>724 211 528</b>	8.200
193 - 203	10.0	<b>724 211 544</b>	8.200
200 - 210	10.0	<b>724 211 560</b>	9.100
209 - 220	10.0	<b>724 211 576</b>	9.100
215 - 226	10.0	<b>724 211 592</b>	9.100
219 - 230	10.0	<b>724 211 608</b>	9.100
222 - 233	10.0	<b>724 211 624</b>	9.100
228 - 240	10.0	<b>724 211 640</b>	9.300
243 - 253	10.0	<b>724 211 656</b>	9.300
252 - 262	10.0	<b>724 211 672</b>	10.600
261 - 271	10.0	<b>724 211 688</b>	10.600
271 - 281	10.0	<b>724 211 704</b>	10.600
280 - 290	10.0	<b>724 211 720</b>	10.600
294 - 304	10.0	<b>724 211 736</b>	10.600
300 - 310	10.0	<b>724 211 752</b>	11.600
310 - 320	10.0	<b>724 211 768</b>	11.600
315 - 326	10.0	<b>724 211 784</b>	11.600
320 - 330	10.0	<b>724 211 800</b>	11.600
324 - 334	10.0	<b>724 211 816</b>	11.600
335 - 346	10.0	<b>724 211 832</b>	11.600

PF 1 54 325 009



## Multi/Clamp Single length 600 mm

### Model:

- Single band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
222 - 233	10.0	<b>724 211 625</b>	10.900
228 - 240	10.0	<b>724 211 641</b>	11.100
243 - 253	10.0	<b>724 211 657</b>	11.100
252 - 262	10.0	<b>724 211 673</b>	12.700
261 - 271	10.0	<b>724 211 689</b>	12.700
271 - 281	10.0	<b>724 211 705</b>	12.700
280 - 290	10.0	<b>724 211 721</b>	12.700
294 - 304	10.0	<b>724 211 737</b>	12.700
300 - 310	10.0	<b>724 211 753</b>	14.200
310 - 320	10.0	<b>724 211 769</b>	14.200
315 - 326	10.0	<b>724 211 785</b>	14.200
320 - 330	10.0	<b>724 211 801</b>	14.200
324 - 334	10.0	<b>724 211 817</b>	14.200
335 - 346	10.0	<b>724 211 833</b>	14.200

PF 1 54 325 009



## Multi/Clamp Double length 200 mm

### Model:

- Double band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg	
88 - 110	16.0	<b>724 212 058</b>	3.300	
108 - 128	16.0	<b>724 212 074</b>	3.400	
112 - 134	16.0	<b>724 212 090</b>	3.400	
120 - 140	16.0	<b>724 212 106</b>	3.400	
133 - 155	16.0	<b>724 212 122</b>	3.800	
138 - 160	16.0	<b>724 212 138</b>	3.800	
158 - 180	16.0	<b>724 212 154</b>	4.400	
168 - 190	16.0	<b>724 212 170</b>	4.400	
190 - 210	10.0	<b>724 212 186</b>	4.700	
195 - 217	10.0	<b>724 212 202</b>	4.700	
210 - 230	10.0	<b>724 212 218</b>	4.900	
216 - 238	10.0	<b>724 212 234</b>	4.900	
225 - 246	10.0	<b>724 212 250</b>	5.100	
238 - 260	10.0	<b>724 212 266</b>	5.100	
251 - 271	10.0	<b>724 212 282</b>	5.300	
260 - 280	10.0	<b>724 212 298</b>	5.300	
269 - 289	10.0	<b>724 212 314</b>	5.300	
273 - 293	10.0	<b>724 212 330</b>	5.300	
295 - 315	10.0	<b>724 212 346</b>	5.300	

PF 1 54 325 009



## Multi/Clamp Double length 250 mm

### Model:

- Double band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg	
88 - 110	16.0	<b>724 212 059</b>	4.500	
108 - 128	16.0	<b>724 212 075</b>	4.700	
112 - 134	16.0	<b>724 212 091</b>	4.700	
120 - 140	16.0	<b>724 212 107</b>	4.700	
133 - 155	16.0	<b>724 212 123</b>	5.200	
138 - 160	16.0	<b>724 212 139</b>	5.200	
158 - 180	16.0	<b>724 212 155</b>	6.000	
168 - 190	16.0	<b>724 212 171</b>	6.000	
190 - 210	10.0	<b>724 212 187</b>	6.400	
195 - 217	10.0	<b>724 212 203</b>	6.400	
210 - 230	10.0	<b>724 212 219</b>	6.600	
216 - 238	10.0	<b>724 212 235</b>	6.600	
225 - 246	10.0	<b>724 212 251</b>	6.900	
238 - 260	10.0	<b>724 212 267</b>	6.900	
251 - 271	10.0	<b>724 212 283</b>	7.200	
260 - 280	10.0	<b>724 212 299</b>	7.200	
269 - 289	10.0	<b>724 212 315</b>	7.200	
273 - 293	10.0	<b>724 212 331</b>	7.200	
295 - 315	10.0	<b>724 212 347</b>	7.200	
314 - 335	10.0	<b>724 212 363</b>	7.400	
322 - 344	10.0	<b>724 212 379</b>	7.400	
334 - 354	10.0	<b>724 212 395</b>	7.400	
340 - 360	10.0	<b>724 212 411</b>	7.400	

PF 1 54 325 009



## Multi/Clamp Double length 300 mm

### Model:

- Double band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
88 - 110	16.0	<b>724 212 060</b>	5.000
108 - 128	16.0	<b>724 212 076</b>	5.300
112 - 134	16.0	<b>724 212 092</b>	5.300
120 - 140	16.0	<b>724 212 108</b>	5.300
133 - 155	16.0	<b>724 212 124</b>	5.800
138 - 160	16.0	<b>724 212 140</b>	5.800
158 - 180	16.0	<b>724 212 156</b>	6.700
168 - 190	16.0	<b>724 212 172</b>	6.700
190 - 210	10.0	<b>724 212 188</b>	7.100
195 - 217	10.0	<b>724 212 204</b>	7.100
210 - 230	10.0	<b>724 212 220</b>	7.500
216 - 238	10.0	<b>724 212 236</b>	7.500
225 - 246	10.0	<b>724 212 252</b>	7.800
238 - 260	10.0	<b>724 212 268</b>	7.800
251 - 271	10.0	<b>724 212 284</b>	8.900
260 - 280	10.0	<b>724 212 300</b>	8.900
269 - 289	10.0	<b>724 212 316</b>	8.900
273 - 293	10.0	<b>724 212 332</b>	8.900
295 - 315	10.0	<b>724 212 348</b>	8.900
314 - 335	10.0	<b>724 212 364</b>	9.500
322 - 344	10.0	<b>724 212 380</b>	9.500
334 - 354	10.0	<b>724 212 396</b>	9.500
340 - 360	10.0	<b>724 212 412</b>	9.500
348 - 368	10.0	<b>724 212 428</b>	10.200
365 - 385	10.0	<b>724 212 444</b>	10.200
376 - 396	10.0	<b>724 212 460</b>	10.200
382 - 402	10.0	<b>724 212 476</b>	10.200
390 - 410	10.0	<b>724 212 492</b>	10.200
404 - 424	10.0	<b>724 212 508</b>	11.000
420 - 440	10.0	<b>724 212 524</b>	11.000

PF 1 54 325 009





## Multi/Clamp Double length 400 mm

### Model:

- Double band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
88 - 110	16.0	<b>724 212 061</b>	6.600
108 - 128	16.0	<b>724 212 077</b>	6.900
112 - 134	16.0	<b>724 212 093</b>	6.900
120 - 140	16.0	<b>724 212 109</b>	6.900
133 - 155	16.0	<b>724 212 125</b>	7.600
138 - 160	16.0	<b>724 212 141</b>	7.600
158 - 180	16.0	<b>724 212 157</b>	8.800
168 - 190	16.0	<b>724 212 173</b>	8.800
190 - 210	10.0	<b>724 212 189</b>	9.400
195 - 217	10.0	<b>724 212 205</b>	9.400
210 - 230	10.0	<b>724 212 221</b>	9.800
216 - 238	10.0	<b>724 212 237</b>	9.800
225 - 246	10.0	<b>724 212 253</b>	10.200
238 - 260	10.0	<b>724 212 269</b>	10.200
251 - 271	10.0	<b>724 212 285</b>	11.500
260 - 280	10.0	<b>724 212 301</b>	11.500
269 - 289	10.0	<b>724 212 317</b>	11.500
273 - 293	10.0	<b>724 212 333</b>	11.500
295 - 315	10.0	<b>724 212 349</b>	11.500
314 - 335	10.0	<b>724 212 365</b>	12.300
322 - 344	10.0	<b>724 212 381</b>	12.300
334 - 354	10.0	<b>724 212 397</b>	12.300
340 - 360	10.0	<b>724 212 413</b>	12.300
348 - 368	10.0	<b>724 212 429</b>	13.200
365 - 385	10.0	<b>724 212 445</b>	13.200
376 - 396	10.0	<b>724 212 461</b>	13.200
382 - 402	10.0	<b>724 212 477</b>	13.200
390 - 410	10.0	<b>724 212 493</b>	13.200
404 - 424	10.0	<b>724 212 509</b>	14.200
420 - 440	10.0	<b>724 212 525</b>	14.200
440 - 460	10.0	<b>724 212 541</b>	14.200
457 - 477	10.0	<b>724 212 557</b>	14.800
468 - 488	10.0	<b>724 212 573</b>	14.800
488 - 508	10.0	<b>724 212 589</b>	14.800
500 - 520	10.0	<b>724 212 605</b>	15.900
520 - 540	6.0	<b>724 212 621</b>	15.900
527 - 547	6.0	<b>724 212 637</b>	15.900
545 - 565	6.0	<b>724 212 653</b>	15.900
555 - 570	6.0	<b>724 212 669</b>	15.900
568 - 588	6.0	<b>724 212 685</b>	15.900
586 - 606	6.0	<b>724 212 701</b>	15.900
600 - 620	6.0	<b>724 212 717</b>	17.700
625 - 645	6.0	<b>724 212 733</b>	17.700
650 - 670	6.0	<b>724 212 749</b>	17.700

PF 1 54 325 009



## Multi/Clamp Double length 500 mm

### Model:

- Double band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
88 - 110	16.0	<b>724 212 062</b>	8.400
108 - 128	16.0	<b>724 212 078</b>	8.800
112 - 134	16.0	<b>724 212 094</b>	8.800
120 - 140	16.0	<b>724 212 110</b>	8.800
133 - 155	16.0	<b>724 212 126</b>	9.600
138 - 160	16.0	<b>724 212 142</b>	9.600
158 - 180	16.0	<b>724 212 158</b>	11.200
168 - 190	16.0	<b>724 212 174</b>	11.200
190 - 210	10.0	<b>724 212 190</b>	12.100
195 - 217	10.0	<b>724 212 206</b>	12.100
210 - 230	10.0	<b>724 212 222</b>	12.500
216 - 238	10.0	<b>724 212 238</b>	12.500
225 - 246	10.0	<b>724 212 254</b>	13.000
238 - 260	10.0	<b>724 212 270</b>	13.000
251 - 271	10.0	<b>724 212 286</b>	15.200
260 - 280	10.0	<b>724 212 302</b>	15.200
269 - 289	10.0	<b>724 212 318</b>	15.200
273 - 293	10.0	<b>724 212 334</b>	15.200
295 - 315	10.0	<b>724 212 350</b>	15.200
314 - 335	10.0	<b>724 212 366</b>	16.100
322 - 344	10.0	<b>724 212 382</b>	16.100
334 - 354	10.0	<b>724 212 398</b>	16.100
340 - 360	10.0	<b>724 212 414</b>	16.100
348 - 368	10.0	<b>724 212 430</b>	17.200
365 - 385	10.0	<b>724 212 446</b>	17.200
376 - 396	10.0	<b>724 212 462</b>	17.200
382 - 402	10.0	<b>724 212 478</b>	17.200
390 - 410	10.0	<b>724 212 494</b>	17.200
404 - 424	10.0	<b>724 212 510</b>	18.700
420 - 440	10.0	<b>724 212 526</b>	18.700
440 - 460	10.0	<b>724 212 542</b>	18.700
457 - 477	10.0	<b>724 212 558</b>	19.200
468 - 488	10.0	<b>724 212 574</b>	19.200
488 - 508	10.0	<b>724 212 590</b>	19.200
500 - 520	10.0	<b>724 212 606</b>	20.700
520 - 540	6.0	<b>724 212 622</b>	20.700
527 - 547	6.0	<b>724 212 638</b>	20.700
545 - 565	6.0	<b>724 212 654</b>	20.700
555 - 570	6.0	<b>724 212 670</b>	20.700
568 - 588	6.0	<b>724 212 686</b>	20.700
586 - 606	6.0	<b>724 212 702</b>	20.700
600 - 620	6.0	<b>724 212 718</b>	22.900
625 - 645	6.0	<b>724 212 734</b>	22.900
650 - 670	6.0	<b>724 212 750</b>	22.900

PF 1 54 325 009



## Multi/Clamp Double length 600 mm

### Model:

- Double band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
314 - 335	10.0	<b>724 212 367</b>	19.000
322 - 344	10.0	<b>724 212 383</b>	19.000
334 - 354	10.0	<b>724 212 399</b>	19.000
340 - 360	10.0	<b>724 212 415</b>	19.000
348 - 368	10.0	<b>724 212 431</b>	20.500
365 - 385	10.0	<b>724 212 447</b>	20.500
376 - 396	10.0	<b>724 212 463</b>	20.500
382 - 402	10.0	<b>724 212 479</b>	20.500
390 - 410	10.0	<b>724 212 495</b>	20.500
404 - 424	10.0	<b>724 212 511</b>	21.800
420 - 440	10.0	<b>724 212 527</b>	21.800
440 - 460	10.0	<b>724 212 543</b>	21.800
457 - 477	10.0	<b>724 212 559</b>	23.000
468 - 488	10.0	<b>724 212 575</b>	23.000
488 - 508	10.0	<b>724 212 591</b>	23.000
500 - 520	10.0	<b>724 212 607</b>	24.500
520 - 540	6.0	<b>724 212 623</b>	24.500
527 - 547	6.0	<b>724 212 639</b>	24.500
545 - 565	6.0	<b>724 212 655</b>	24.500
555 - 570	6.0	<b>724 212 671</b>	24.500
568 - 588	6.0	<b>724 212 687</b>	24.500
586 - 606	6.0	<b>724 212 703</b>	24.500
600 - 620	6.0	<b>724 212 719</b>	27.200
625 - 645	6.0	<b>724 212 735</b>	27.200
650 - 670	6.0	<b>724 212 751</b>	27.200
705 - 725	4.0	<b>724 212 767</b>	19.700
730 - 750	4.0	<b>724 212 783</b>	29.200
755 - 775	4.0	<b>724 212 799</b>	29.200
805 - 825	3.0	<b>724 212 815</b>	30.500
835 - 855	3.0	<b>724 212 831</b>	31.500

PF 1 54 325 009



## Multi/Clamp Double length 750 mm

### Model:

- Double band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
420 - 440	10.0	<b>724 212 528</b>	26.300
440 - 460	10.0	<b>724 212 544</b>	26.300
457 - 477	10.0	<b>724 212 560</b>	28.500
468 - 488	10.0	<b>724 212 576</b>	28.500
488 - 508	10.0	<b>724 212 592</b>	28.500
500 - 520	10.0	<b>724 212 608</b>	30.900
520 - 540	6.0	<b>724 212 624</b>	30.900
527 - 547	6.0	<b>724 212 640</b>	30.900
545 - 565	6.0	<b>724 212 656</b>	30.900
555 - 570	6.0	<b>724 212 672</b>	30.900
568 - 588	6.0	<b>724 212 688</b>	30.900
586 - 606	6.0	<b>724 212 704</b>	30.900
600 - 620	6.0	<b>724 212 720</b>	34.500
625 - 645	6.0	<b>724 212 736</b>	34.500
650 - 670	6.0	<b>724 212 752</b>	34.500
705 - 725	4.0	<b>724 212 768</b>	24.900
730 - 750	4.0	<b>724 212 784</b>	36.500
755 - 775	4.0	<b>724 212 800</b>	36.500
805 - 825	3.0	<b>724 212 816</b>	38.000
835 - 855	3.0	<b>724 212 832</b>	39.000

PF 1 54 325 009



## Multi/Clamp Triple length 300 mm

### Model:

- Triple band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
267 - 297	10.0	<b>724 213 060</b>	9.000
300 - 330	10.0	<b>724 213 076</b>	10.200
323 - 353	10.0	<b>724 213 092</b>	10.200
352 - 382	10.0	<b>724 213 108</b>	10.500
378 - 408	10.0	<b>724 213 124</b>	12.000
402 - 432	10.0	<b>724 213 140</b>	12.000
429 - 459	10.0	<b>724 213 156</b>	12.000
456 - 486	10.0	<b>724 213 172</b>	12.900
490 - 520	10.0	<b>724 213 188</b>	14.100
520 - 550	10.0	<b>724 213 204</b>	14.700

PF 1 54 325 009



## Multi/Clamp Triple length 400 mm

### Model:

- Triple band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
267 - 297	10.0	<b>724 213 061</b>	11.700
300 - 330	10.0	<b>724 213 077</b>	13.500
323 - 353	10.0	<b>724 213 093</b>	13.500
352 - 382	10.0	<b>724 213 109</b>	14.100
378 - 408	10.0	<b>724 213 125</b>	15.600
402 - 432	10.0	<b>724 213 141</b>	15.600
429 - 459	10.0	<b>724 213 157</b>	15.600
456 - 486	10.0	<b>724 213 173</b>	16.800
490 - 520	10.0	<b>724 213 189</b>	17.700
520 - 550	10.0	<b>724 213 205</b>	19.200
532 - 562	6.0	<b>724 213 221</b>	19.200
545 - 575	6.0	<b>724 213 237</b>	19.200
570 - 600	6.0	<b>724 213 253</b>	19.200

PF 1 54 325 009



## Multi/Clamp Triple length 500 mm

### Model:

- Triple band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
352 - 382	10.0	<b>724 213 110</b>	15.600
378 - 408	10.0	<b>724 213 126</b>	20.100
402 - 432	10.0	<b>724 213 142</b>	20.100
429 - 459	10.0	<b>724 213 158</b>	20.100
456 - 486	10.0	<b>724 213 174</b>	21.600
490 - 520	10.0	<b>724 213 190</b>	23.400
520 - 550	10.0	<b>724 213 206</b>	24.600
532 - 562	6.0	<b>724 213 222</b>	24.600
545 - 575	6.0	<b>724 213 238</b>	24.600
570 - 600	6.0	<b>724 213 254</b>	24.600
586 - 616	6.0	<b>724 213 270</b>	24.600
609 - 639	6.0	<b>724 213 286</b>	26.000
615 - 645	6.0	<b>724 213 302</b>	26.000

table continued next page

PF 1 54 325 009

Range [mm]	PN Water [bar]	NBR Code	kg
633 - 663	4.0	<b>724 213 318</b>	26.000
640 - 670	4.0	<b>724 213 334</b>	26.000
654 - 684	4.0	<b>724 213 350</b>	26.000



## Multi/Clamp Triple length 600 mm

### Model:

- Triple band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
456 - 486	10.0	<b>724 213 175</b>	25.800
490 - 520	10.0	<b>724 213 191</b>	27.300
520 - 550	10.0	<b>724 213 207</b>	30.000
532 - 562	6.0	<b>724 213 223</b>	30.000
545 - 575	6.0	<b>724 213 239</b>	30.000
570 - 600	6.0	<b>724 213 255</b>	30.000
586 - 616	6.0	<b>724 213 271</b>	30.000
609 - 639	6.0	<b>724 213 287</b>	32.000
615 - 645	6.0	<b>724 213 303</b>	32.000
633 - 663	4.0	<b>724 213 319</b>	32.000
640 - 670	4.0	<b>724 213 335</b>	32.000
654 - 684	4.0	<b>724 213 351</b>	32.000
670 - 700	4.0	<b>724 213 367</b>	32.000
702 - 732	4.0	<b>724 213 383</b>	35.000
711 - 741	4.0	<b>724 213 399</b>	35.000
729 - 759	4.0	<b>724 213 415</b>	35.000
747 - 777	4.0	<b>724 213 431</b>	35.000
780 - 815	4.0	<b>724 213 447</b>	38.000
800 - 830	4.0	<b>724 213 463</b>	38.000
813 - 843	3.0	<b>724 213 479</b>	38.000
830 - 860	3.0	<b>724 213 495</b>	38.000
852 - 882	2.0	<b>724 213 511</b>	38.000
864 - 894	2.0	<b>724 213 527</b>	38.000
900 - 930	2.0	<b>724 213 543</b>	40.000
925 - 955	2.0	<b>724 213 559</b>	40.000
945 - 975	2.0	<b>724 213 575</b>	40.000
970 - 1000	2.0	<b>724 213 591</b>	40.000

PF 1 54 325 009



## Multi/Clamp Triple length 750 mm

### Model:

- Triple band clamp with full circle gasket
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	kg
545 - 575	6.0	<b>724 213 240</b>	39.000
570 - 600	6.0	<b>724 213 256</b>	39.000
586 - 616	6.0	<b>724 213 272</b>	39.000
609 - 639	6.0	<b>724 213 288</b>	41.000
615 - 645	6.0	<b>724 213 304</b>	41.000
633 - 663	4.0	<b>724 213 320</b>	41.000
640 - 670	4.0	<b>724 213 336</b>	41.000
654 - 684	4.0	<b>724 213 352</b>	41.000
670 - 700	4.0	<b>724 213 368</b>	41.000
702 - 732	4.0	<b>724 213 384</b>	44.000
711 - 741	4.0	<b>724 213 400</b>	44.000
729 - 759	4.0	<b>724 213 416</b>	44.000
747 - 777	4.0	<b>724 213 432</b>	44.000

table continued next page

<b>Range</b> [mm]	<b>PN Water</b> [bar]	<b>NBR</b> <b>Code</b>	<b>kg</b>	
780 - 815	4.0	<b>724 213 448</b>	47.000	
800 - 730	4.0	<b>724 213 464</b>	47.000	
813 - 843	3.0	<b>724 213 480</b>	47.000	
830 - 860	3.0	<b>724 213 496</b>	47.000	
852 - 882	2.0	<b>724 213 512</b>	47.000	
864 - 894	2.0	<b>724 213 528</b>	47.000	
900 - 930	2.0	<b>724 213 544</b>	49.000	
925 - 955	2.0	<b>724 213 560</b>	49.000	
945 - 975	2.0	<b>724 213 576</b>	49.000	
970 - 1000	2.0	<b>724 213 592</b>	49.000	

PF 1 54 325 009

## Multi/Clamp Thread (surcharge)



### Model:

- The Multi/Clamp Single, Double and Triple can be equipped with a threaded outlet
- To obtain the total product price please take the surcharge for the threaded outlet and the price of the repair clamp
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- Female threaded outlet (other threads or combinations on request)

Inch	threaded outlet	Length	Code
1/2	from 48 mm	min. width 150 mm	<b>thread1/2</b>
3/4	from 48 mm	min. width 150 mm	<b>thread3/4</b>
1	from 54 mm	min. width 150 mm	<b>thread1</b>
1 1/4	from 76 mm	min. width 150 mm	<b>thread1.1/4</b>
1 1/2	from 82 mm	min. width 200 mm	<b>thread1.1/2</b>
2	from 87 mm	min. width 200 mm	<b>thread2</b>
2 1/2	from 110 mm	min. width 200 mm	<b>thread2.1/2</b>
3	from 130 mm	min. width 300 mm	<b>thread3</b>
4	from 155 mm	min. width 400 mm	<b>thread4</b>



## Multi/Clamp Saddle Studs threaded outlet 1/2"

### Model:

- Saddle with threaded outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Outlet dimension up to 4" available on request
- Lower shell half is without gasket (available on request)
- Other sizes available on request

Range [mm]	PN Water [bar]	NBR Code	kg
68 - 78	16.0	<b>724 201 061</b>	1.000
88 - 110	16.0	<b>724 201 073</b>	1.000
108 - 134	16.0	<b>724 201 097</b>	1.000
133 - 155	16.0	<b>724 201 133</b>	1.000
159 - 181	16.0	<b>724 201 169</b>	1.000
168 - 190	16.0	<b>724 201 193</b>	1.000
190 - 212	16.0	<b>724 201 205</b>	1.000
216 - 238	16.0	<b>724 201 217</b>	1.000
238 - 260	16.0	<b>724 201 241</b>	1.000
267 - 289	16.0	<b>724 201 253</b>	1.000

PF 1 54 327 011



## Multi/Clamp Saddle Studs threaded outlet 3/4"

### Model:

- Saddle with threaded outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Outlet dimension up to 4" available on request
- Lower shell half is without gasket (available on request)
- Other sizes available on request

Range [mm]	PN Water [bar]	NBR Code	kg
68 - 78	16.0	<b>724 201 062</b>	1.000
88 - 110	16.0	<b>724 201 074</b>	1.000
108 - 134	16.0	<b>724 201 098</b>	1.000

table continued next page



Range [mm]	PN Water [bar]	NBR Code	kg
133 - 155	16.0	<b>724 201 134</b>	1.000
159 - 181	16.0	<b>724 201 170</b>	1.000
168 - 190	16.0	<b>724 201 194</b>	1.000
190 - 212	16.0	<b>724 201 206</b>	1.000
216 - 238	16.0	<b>724 201 218</b>	1.000
238 - 260	16.0	<b>724 201 242</b>	1.000
267 - 289	16.0	<b>724 201 254</b>	1.000

PF 1 54 327 011



## Multi/Clamp Saddle Studs threaded outlet 1"

### Model:

- Saddle with threaded outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Outlet dimension up to 4" available on request
- Lower shell half is without gasket (available on request)
- Other sizes available on request

Range [mm]	PN Water [bar]	NBR Code	kg
68 - 78	16.0	<b>724 201 063</b>	1.000
88 - 110	16.0	<b>724 201 075</b>	1.000
108 - 134	16.0	<b>724 201 099</b>	1.000
133 - 155	16.0	<b>724 201 135</b>	1.000
159 - 181	16.0	<b>724 201 171</b>	1.000
168 - 190	16.0	<b>724 201 195</b>	1.000
190 - 212	16.0	<b>724 201 207</b>	1.000
216 - 238	16.0	<b>724 201 219</b>	1.000
238 - 260	16.0	<b>724 201 243</b>	1.000
267 - 289	16.0	<b>724 201 255</b>	1.000

PF 1 54 327 011



## Multi/Clamp Saddle Studs threaded outlet 1 1/4"

### Model:

- Saddle with threaded outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Outlet dimension up to 4" available on request
- Lower shell half is without gasket (available on request)
- Other sizes available on request

Range [mm]	PN Water [bar]	NBR Code	kg
88 - 110	16.0	<b>724 201 076</b>	1.000
108 - 134	16.0	<b>724 201 100</b>	1.000
133 - 155	16.0	<b>724 201 136</b>	1.000
159 - 181	16.0	<b>724 201 172</b>	1.000
168 - 190	16.0	<b>724 201 196</b>	1.000
190 - 212	16.0	<b>724 201 208</b>	1.000
216 - 238	16.0	<b>724 201 220</b>	1.000
238 - 260	16.0	<b>724 201 244</b>	1.000
267 - 289	16.0	<b>724 201 256</b>	1.000

PF 1 54 327 011



## Multi/Clamp Saddle Studs threaded outlet 1 1/2"

### Model:

- Saddle with threaded outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Outlet dimension up to 4" available on request
- Lower shell half is without gasket (available on request)
- Other sizes available on request

Range [mm]	PN Water [bar]	NBR Code	kg
108 - 134	16.0	<b>724 201 101</b>	1.000
133 - 155	16.0	<b>724 201 137</b>	1.000
159 - 181	16.0	<b>724 201 173</b>	1.000
168 - 190	16.0	<b>724 201 197</b>	1.000
190 - 212	16.0	<b>724 201 209</b>	1.000
216 - 238	16.0	<b>724 201 221</b>	1.000
238 - 260	16.0	<b>724 201 245</b>	1.000
267 - 289	16.0	<b>724 201 257</b>	1.000

PF 1 54 327 011



## Multi/Clamp Saddle Studs threaded outlet 2"

### Model:

- Saddle with threaded outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Outlet dimension up to 4" available on request
- Lower shell half is without gasket (available on request)
- Other sizes available on request

Range [mm]	PN Water [bar]	NBR Code	kg
108 - 134	16.0	<b>724 201 102</b>	1.000
133 - 155	16.0	<b>724 201 138</b>	1.000
159 - 181	16.0	<b>724 201 174</b>	1.000
168 - 190	16.0	<b>724 201 198</b>	1.000
190 - 212	16.0	<b>724 201 210</b>	1.000
216 - 238	16.0	<b>724 201 222</b>	1.000
238 - 260	16.0	<b>724 201 246</b>	1.000
267 - 289	16.0	<b>724 201 258</b>	1.000

PF 1 54 327 011



## Multi/Clamp Flange (tapping sleeve) length 200 mm

### Model:

- Double band saddle with flanged outlet
- Full circle construction for optimal pipe support
- To obtain the total product price, please take the price of the tapping sleeve and add the price for the flange outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	PN Water [bar]	NBR Code	
95 - 104	16.0	<b>95-104L200N</b>	
98 - 108	16.0	<b>98-108L200N</b>	
108 - 128	16.0	<b>108-128L200N</b>	
118 - 138	16.0	<b>118-138L200N</b>	
133 - 153	16.0	<b>133-153L200N</b>	
143 - 163	16.0	<b>143-163L200N</b>	
160 - 180	16.0	<b>160-180L200N</b>	
180 - 200	16.0	<b>180-200L200N</b>	
190 - 210	16.0	<b>190-210L200N</b>	
210 - 230	16.0	<b>210-230L200N</b>	
230 - 250	16.0	<b>230-250L200N</b>	
240 - 260	16.0	<b>240-260L200N</b>	
250 - 270	16.0	<b>250-270L200N</b>	
270 - 290	16.0	<b>270-290L200N</b>	
290 - 310	16.0	<b>290-310L200N</b>	



## Multi/Clamp Flange (tapping sleeve) length 300 mm

### Model:

- Double band saddle with flanged outlet
- Full circle construction for optimal pipe support
- To obtain the total product price, please take the price of the tapping sleeve and add the price for the flange outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	DN [mm]	PN Water [bar]	NBR Code	
95 - 104		16.0	<b>95-104L300N</b>	
98 - 108		16.0	<b>98-108L300N</b>	
108 - 128		16.0	<b>108-128L300N</b>	
118 - 138		16.0	<b>118-138L300N</b>	
133 - 153		16.0	<b>133-153L300N</b>	
143 - 163		16.0	<b>143-163L300N</b>	
160 - 180		16.0	<b>160-180L300N</b>	
180 - 200		16.0	<b>180-200L300N</b>	
190 - 210		16.0	<b>190-210L300N</b>	
210 - 230		16.0	<b>210-230L300N</b>	
230 - 250		16.0	<b>230-250L300N</b>	
240 - 260		16.0	<b>240-260L300N</b>	
250 - 270		16.0	<b>250-270L300N</b>	
270 - 290		16.0	<b>270-290L300N</b>	
290 - 310		16.0	<b>290-310L300N</b>	
315 - 335		16.0	<b>315-335L300N</b>	
335 - 355		16.0	<b>335-355L300N</b>	
-	350	16.0	<b>DN350L300N</b>	



## Multi/Clamp Flange (tapping sleeve) length 400 mm

### Model:

- Double band saddle with flanged outlet
- Full circle construction for optimal pipe support
- To obtain the total product price, please take the price of the tapping sleeve and add the price for the flange outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	DN [mm]	PN Water [bar]	NBR Code
95 - 104		16.0	<b>95-104L400N</b>
98 - 108		16.0	<b>98-108L400N</b>
108 - 128		16.0	<b>108-128L400N</b>
118 - 138		16.0	<b>118-138L400N</b>
133 - 153		16.0	<b>133-153L400N</b>
143 - 163		16.0	<b>143-163L400N</b>
160 - 180		16.0	<b>160-180L400N</b>
180 - 200		16.0	<b>180-200L400N</b>
190 - 210		16.0	<b>190-210L400N</b>
210 - 230		16.0	<b>210-230L400N</b>
230 - 250		16.0	<b>230-250L400N</b>
240 - 260		16.0	<b>240-260L400N</b>
250 - 270		16.0	<b>250-270L400N</b>
270 - 290		16.0	<b>270-290L400N</b>
290 - 310		16.0	<b>290-310L400N</b>
315 - 335		16.0	<b>315-335L400N</b>
335 - 355		16.0	<b>335-355L400N</b>
- 350		16.0	<b>DN350L400N</b>
- 400		16.0	<b>DN400L400N</b>
- 450		16.0	<b>DN450L400N</b>
- 500		16.0	<b>DN500L400N</b>
- 600		10.0	<b>DN600L400N</b>
- 700			<b>DN700L400N</b>



## Multi/Clamp Flange (tapping sleeve) length 500 mm

### Model:

- Double band saddle with flanged outlet
- Full circle construction for optimal pipe support
- To obtain the total product price, please take the price of the tapping sleeve and add the price for the flange outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	DN [mm]	PN Water [bar]	NBR Code
95 - 104		16.0	<b>95-104L500N</b>
98 - 108		16.0	<b>98-108L500N</b>
108 - 128		16.0	<b>108-128L500N</b>
118 - 138		16.0	<b>118-138L500N</b>
133 - 153		16.0	<b>133-153L500N</b>
143 - 163		16.0	<b>143-163L500N</b>
160 - 180		16.0	<b>160-180L500N</b>
180 - 200		16.0	<b>180-200L500N</b>
190 - 210		16.0	<b>190-210L500N</b>
210 - 230		16.0	<b>210-230L500N</b>
230 - 250		16.0	<b>230-250L500N</b>
240 - 260		16.0	<b>240-260L500N</b>
250 - 270		16.0	<b>250-270L500N</b>
270 - 290		16.0	<b>270-290L500N</b>
290 - 310		16.0	<b>290-310L500N</b>
315 - 335		16.0	<b>315-335L500N</b>
335 - 355		16.0	<b>335-355L500N</b>
- 350		16.0	<b>DN350L500N</b>

table continued next page

Range [mm]	DN [mm]	PN Water [bar]	NBR Code
-	400	16.0	DN400L500N
-	450	16.0	DN450L500N
-	500	16.0	DN500L500N
-	600	10.0	DN600L500N
-	700		DN700L500N
-	750		DN750L500N
-	800		DN800L500N



## Multi/Clamp Flange (tapping sleeve) length 600 mm

### Model:

- Double band saddle with flanged outlet
- Full circle construction for optimal pipe support
- To obtain the total product price, please take the price of the tapping sleeve and add the price for the flange outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

Range [mm]	DN [mm]	PN Water [bar]	NBR Code
315 - 335		16.0	315-335L600N
335 - 355		16.0	335-355L600N
-	350	16.0	DN350L600N
-	400	16.0	DN400L600N
-	450	16.0	DN450L600N
-	500	16.0	DN500L600N
-	600	10.0	DN600L600N
-	700		DN700L600N
-	750		DN750L600N
-	800		DN800L600N



## Multi/Clamp Flange (tapping sleeve) length 750 mm

### Model:

- Double band saddle with flanged outlet
- Full circle construction for optimal pipe support
- To obtain the total product price, please take the price of the tapping sleeve and add the price for the flange outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

DN [mm]	PN Water [bar]	NBR Code
400	16.0	DN400L750N
450	16.0	DN450L750N
500	16.0	DN500L750N
600	10.0	DN600L750N
700		DN700L750N
750		DN750L750N
800		DN800L750N

## Multi/Clamp Flange (flange outlet)



### Model:

- To obtain the total product price please add the price of the tapping sleeve
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)

DN [mm]	Drilling pattern	required body length	Code
50	PN 10/16	200 mm	<b>flangeDN50</b>
65	PN 10/16	300 mm	<b>flangeDN65</b>
80	PN 10/16	300 mm (400 mm if POD > 300)	<b>flangeDN80</b>
100	PN 10/16	400 mm	<b>flangeDN100</b>
125	PN 10/16	400 mm	<b>flangeDN125</b>
150	PN 10/16	400 mm	<b>flangeDN150</b>
200	PN 10	500 mm	<b>flangeDN200</b>
250	PN 10	600 mm	<b>flangeDN250</b>
300	PN 10	750 mm	<b>flangeDN300</b>



## Multi/Clamp Combi Box length 400 mm

### Model:

- A combination of either two or more shell sections enables you to repair pipes from 213 mm up to 1146 mm OD
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)

description	NBR A2 Code	kg
repair set complete (all shell sections + wooden box)	<b>724 213 730</b>	46.700
shell section A	<b>724 213 746</b>	5.000
shell section B	<b>724 213 762</b>	5.300
shell section C	<b>724 213 778</b>	5.700
shell section D	<b>724 213 794</b>	6.100
shell section E	<b>724 213 810</b>	6.700
wooden box separate	<b>724 213 826</b>	17.900

Range (mm)	description
	<u>shell sections to combine with 1 Multi/Clamp Combi box:</u>
213 - 233	A B
233 - 253	A C
253 - 273	B C
264 - 284	A D
284 - 304	B D
294 - 314	A E
304 - 324	C D
314 - 334	B E
335 - 355	C E
354 - 384	A B C
386 - 416	A B D
406 - 436	A C D
416 - 446	A B E
426 - 456	B C D
436 - 466	A C E
456 - 486	B C E
467 - 497	A D E
487 - 517	B D E
508 - 538	C D E
527 - 567	A B C D
558 - 598	A B C E
589 - 629	A B D E
609 - 649	A C D E
629 - 669	B C D E
	<u>shell sections to combine with 2 Multi/Clamp Combi boxes:</u>
720 - 770	E E B A A
761 - 811	E E C B A
832 - 882	E E D C B
853 - 903	E E D C C
934 - 994	E E D C B A
965 - 1025	E E D D B A
1026 - 1086	E E D D C C
1076 - 1146	E E D C C B A

PF 1 54 325 009

