



## Multi/Saddle Plus

### → Your benefits

- Easy installation
- Complete saddle program
- High quality connection
- Stock reduction thanks to universal saddles
- Easy stacking thanks to compact packing
- Suitable for all pipe materials; except PE and thin walled PVC (wall thickness less than SDR 13,6)



## Contents Multi/Saddle Plus

	page
Multi/Saddle Plus 301	130
Multi/Saddle Plus 201	130
Multi/Saddle Plus 200	131
Multi/Saddle Plus Straps	131
Multi/Saddle Plus Spatula	131
Multi/Saddle Plus Hot Tap Adaptors	132
Male threaded adaptors for W400 drilling device	132
Female threaded adaptors for W400 drilling device	132

# Multi/Saddle Plus

## Multi/Saddle Plus 301

saddle range 60-355 mm (to be combined with straps)



### Model:

- With direct PE connection by means of Push-Fit
- With temporary shut-off mechanism by means of spatula (See Multi/Saddle Plus Spatula)
- Ductile Cast iron GGG40 saddle head
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- Stainless steel A2 (AISI 304) band with NBR protection (to be ordered separately)
- Rubber inlay: EPDM for water and NBR for water and gas
- Forged brass insert and nut

### Note:

\*Must be applied for pipes DN80 or larger

Outlet [mm]	EPDM Code	NBR Code	PN Water [bar]	PN Gas [bar]	
25	<b>709 613 752</b>	<b>709 613 852</b>	16.0	5.0	
32	<b>709 613 754</b>	<b>709 613 854</b>	16.0	5.0	
40*	<b>709 613 756</b>	<b>709 613 856</b>	16.0	5.0	
50*	<b>709 613 758</b>	<b>709 613 858</b>	16.0	5.0	

PF 1 54 327 010

## Multi/Saddle Plus 201

saddle range 60-355 mm (to be combined with straps)



### Model:

- With female threaded outlet
- With temporary shut-off mechanism by means of spatula (See Multi/Saddle Plus Spatula)
- Ductile Cast iron GGG40 saddle head
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- Stainless steel A2 (AISI 304) band with NBR protection (to be ordered separately)
- Rubber inlay: EPDM for water and NBR for water and gas

### Note:

\*Must be applied for pipes DN80 or larger

Thread outlet [inch]	EPDM Code	NBR Code	PN Water [bar]	PN Gas [bar]	
1	<b>709 613 734</b>	<b>709 613 834</b>	16.0	5.0	
1 1/4	<b>709 613 736</b>	<b>709 613 836</b>	16.0	5.0	
1 1/2*	<b>709 613 738</b>	<b>709 613 838</b>	16.0	5.0	
2*	<b>709 613 740</b>	<b>709 613 840</b>	16.0	5.0	

PF 1 54 327 010



## Multi/Saddle Plus 200 saddle range 60-355 mm (to be combined with straps)

### Model:

- With female threaded outlet
- Ductile Cast iron GGG40 saddle head
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- Stainless steel A2 (AISI 304) band with NBR protection (to be ordered separately)
- Rubber inlay: EPDM for water and NBR for water and gas

### Note:

\*Must be applied for pipes DN80 or larger

Thread outlet [inch]	EPDM Code	NBR Code	PN Water [bar]	PN Gas [bar]
1	<b>709 613 714</b>	<b>709 613 814</b>	16.0	5.0
1 1/4	<b>709 613 716</b>	<b>709 613 816</b>	16.0	5.0
1 1/2*	<b>709 613 718</b>	<b>709 613 818</b>	16.0	5.0
2*	<b>709 613 720</b>	<b>709 613 820</b>	16.0	5.0

PF 1 54 327 010



## Multi/Saddle Plus Straps (to be combined with Multi/Saddle Plus 301, 201 and 200)

### Model:

- Stainless steel A2 (AISI 304) band with NBR protection (to be ordered separately)
- The straps can be combined with all Multi/Saddle Plus types
- Weldfree design avoiding intergranular corrosion
- Range d60 - 355 mm
- Special packaging, flat labelled boxes for easy handling and identification
- Ready to install, studs and nuts in one package

Range [mm]	Code
60 - 80	<b>709 613 930</b>
70 - 90	<b>709 613 932</b>
90 - 110	<b>709 613 934</b>
110 - 130	<b>709 613 936</b>
130 - 150	<b>709 613 938</b>
145 - 165	<b>709 613 940</b>
160 - 180	<b>709 613 942</b>
175 - 195	<b>709 613 944</b>
190 - 210	<b>709 613 946</b>
205 - 225	<b>709 613 948</b>
220 - 240	<b>709 613 950</b>
235 - 255	<b>709 613 952</b>
250 - 270	<b>709 613 954</b>
270 - 290	<b>709 613 956</b>
285 - 305	<b>709 613 958</b>
300 - 320	<b>709 613 960</b>
315 - 335	<b>709 613 962</b>
335 - 355	<b>709 613 964</b>

PF 1 54 327 010



## Multi/Saddle Plus Spatula

Description	Code
spatula for saddle outlet 1" / d25 + d32	<b>709 613 903</b>
spatula for saddle outlet 1 1/4"	<b>709 613 904</b>
spatula for saddle outlet 1 1/2" / d40 + d50	<b>709 613 905</b>
spatula for saddle outlet 2"	<b>709 613 906</b>

PF 1 54 327 010



PF 1 54 327 010

## Multi/Saddle Plus Hot Tap Adaptors

Description	Code
Hot Tap Adaptor Multi/Saddle Plus 301 PE d25 x 1	<b>709 613 652</b>
Hot Tap Adaptor Multi/Saddle Plus 301 PE d32 x 1	<b>709 613 654</b>
Hot Tap Adaptor Multi/Saddle Plus 301 PE d40 x 1 ½	<b>709 613 656</b>
Hot Tap Adaptor Multi/Saddle Plus 301 PE d50 x 1 ½	<b>709 613 658</b>
Hot Tap Adaptor Multi/Saddle Plus 201 1	<b>709 613 634</b>
Hot Tap Adaptor Multi/Saddle Plus 201 1 ½	<b>709 613 638</b>
Hot Tap Adaptor Multi/Saddle Plus 201 2	<b>709 613 640</b>



PF 1 54 326 005

## Male threaded adaptors for W400 drilling device

### Model:

- Suitable to connect to Multi/Saddle Plus 200 and 201 saddles

Description	Code
male threaded adaptor 3/4	<b>709 702 257</b>
male threaded adaptor 1	<b>709 702 258</b>
male threaded adaptor 1 1/4	<b>709 702 259</b>
male threaded adaptor 1 1/2	<b>709 702 260</b>
male threaded adaptor 2	<b>709 702 261</b>



PF 1 54 326 005

## Female threaded adaptors for W400 drilling device

### Model:

- Suitable to connect to Multi/Saddle Plus 301 saddles

Description	Code
female threaded adaptor d25 + d32	<b>709 702 262</b>
female threaded adaptor d40 + d50	<b>709 702 263</b>