

**WAL/V**

### → Your benefits

- Quick, efficient and reliable solution for under pressure repair of leaking socket and spigot joints made of cast iron, asbestos cement and steel
- Usable for various diameters thanks to adjustable clamping parts
- Durable corrosion protection by Resicoat® epoxy powder coating (GSK approved)
- Reusable
- Applicable for under- and above-ground use



## Contents WAL/V

	page
WAL/V Single	124
WAL/V Double	125

# WAL/V


## WAL/V Single

### Model:

- Ductile Cast iron GGG40 body
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- Gasket: NBR
- Stainless steel A2 quality (AISI 304) bolts, nuts and washers
- Suitable for usage in potable water or gas

### Note:

Other sizes up to DN1200 on request



DN [mm]	Range [mm]	NBR Code	kg	b [mm]	e [mm]	bolt length [mm]	PN Water [bar]	PN Gas [bar]
80	90 - 114	<b>709 016 053</b>	6.500	175	8xM16	140	10.0	4.0
100	110 - 135	<b>709 016 055</b>	7.500	195	8xM16	140	10.0	4.0
125	134 - 156	<b>709 016 060</b>	12.500	240	8xM16	140	10.0	4.0
150	168 - 191	<b>709 016 065</b>	13.000	250	8xM16	140	10.0	4.0
175	204 - 218	<b>709 016 070</b>	15.000	280	8xM16	140	10.0	4.0
200	220 - 253	<b>709 016 075</b>	16.000	315	8xM16	140	10.0	4.0
225	246 - 278	<b>709 016 080</b>	17.000	350	8xM16	140	10.0	4.0
250	265 - 293	<b>709 016 085</b>	18.000	360	8xM16	140	10.0	4.0
300	319 - 348	<b>709 016 095</b>	20.000	435	12xM16	140	10.0	4.0
325	344 - 372	<b>709 016 100</b>	23.000	435	12xM16	140	10.0	4.0
350	374 - 397	<b>709 016 105</b>	27.000	490	12xM16	140	10.0	4.0
400	424 - 453	<b>709 016 110</b>	27.500	545	16xM16	140	10.0	4.0
500	524 - 552	<b>709 016 120</b>	36.000	660	20xM16	140	10.0	4.0
600	627 - 655	<b>709 016 130</b>	42.000	775	20xM16	140	10.0	4.0
625	647 - 675	<b>709 016 131</b>	45.500	775	20xM16	140	10.0	4.0
700	735 - 767	<b>709 016 135</b>	54.000	895	20xM16	140	10.0	4.0

PF 1 54 325 008




## WAL/V Double

### Model:

- Ductile Cast iron GGG40 body
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- Gasket: NBR
- Stainless steel A2 quality (AISI 304) bolts, nuts and washers
- Suitable for usage in potable water or gas

### Note:

Other sizes up to DN1200 on request



DN [mm]	Range [mm]	NBR Code	kg	b [mm]	e [mm]	bolt length [mm]	PN Water [bar]	PN Gas [bar]
80	90 - 114	<b>709 016 701</b>	7.800	125	8xM16	240	10.0	4.0
125	110 - 135	<b>709 016 702</b>	8.800	125	8xM16	240	10.0	4.0
125	134 - 156	<b>709 016 703</b>	14.600	240	8xM16	240	10.0	4.0
125	168 - 191	<b>709 016 704</b>	13.000	250	8xM16	240	10.0	4.0
125	192 - 216	<b>709 016 705</b>	17.000	280	8xM16	240	10.0	4.0
200	220 - 253	<b>709 016 706</b>	20.000	315	8xM16	240	10.0	4.0
225	246 - 278	<b>709 016 707</b>	21.000	350	8xM16	240	10.0	4.0
250	265 - 293	<b>709 016 708</b>	23.000	360	8xM16	240	10.0	4.0
300	319 - 348	<b>709 016 710</b>	23.000	435	12xM16	240	10.0	4.0
325	344 - 372	<b>709 016 711</b>	27.500	435	12xM16	240	10.0	4.0
350	374 - 397	<b>709 016 712</b>	32.000	490	12xM16	240	10.0	4.0
400	424 - 453	<b>709 016 714</b>	33.000	545	16xM16	240	10.0	4.0
500	524 - 552	<b>709 016 715</b>	48.000	660	20xM16	240	10.0	4.0
600	627 - 655	<b>709 016 725</b>	55.000	775	20xM16	240	10.0	4.0
625	647 - 675	<b>709 016 727</b>	59.000	775	20xM16	240	10.0	4.0
700	735 - 767	<b>709 016 735</b>		895	20xM16	240	10.0	4.0

PF 1 54 325 008

